

User Guide

CFT Carpet & Upholstery HD Traffic

22000678/2x5Lt

Application	Removal of Heavily Ingrained Soiling in High Traffic Areas
Features &	Low hazard & powerful
Benefits	Reduced colour-bleed
	 Excellent soil wetting and dispersion
Dilution	Normal Soiling: 2% (20 ml made up to 1litre)
	Heavy Soiling: 20%(200 ml made up to 1litre)
Equipment	• Sprayer: recommend pressure sprayer set at approx 2 bar.
Required	Extraction machine
Use Instructions	Dilute the CFT Carpet & Upholstery HD Traffic accordingly with water and fill up the pressure sprayer.
	Prepare the area for wet cleaning.
	Spray CFT C&U HD Traffic evenly across the surface. This should be wet not saturated.
	Using either a rotary scrubber or a brush agitate the area.
	Allow up to five minutes dwell time.
	Extract and rinse using CFT Fibre and Fabric Rinse or spray on to neutralise.
	This should be used in conjunction with CFT Carpet and Upholstery MP or CFT Super Plus.
Hints & Tips	On large carpets or where there is a risk of drying before extraction – divide carpet into smaller areas completing whole process before moving to the next area.
Precautions	Use all PPE advised in MSDS and COSHH Assessment
	Test a small inconspicuous area. Check the carpet construction and pile type before wetting.