

## **User Guide**

## **Fleet Clean NC**

22001096/20Lt 22001097/205Lt 22001098/1000Lt IBC

2200109	96/20Lt 22001097/205Lt 22001098/1000Lt IBC
Application	Non-Caustic Standard Vehicle Wash
Features & Benefits	Caustic Free – safer to use
	<ul> <li>Excellent performance on all vehicle types</li> </ul>
	Biodegradable formulation
	Versatile – manual or pressure washer use
Dilution	Light Soiling: 1% (100:1)
	Medium Soiling 2% (50:1)
	Heavy Soiling 3% (30:1)
<b>Equipment Required</b>	Pressure washer
	Suitable dilution vessel
	Bucket/Mop
	Water supply
Use Instructions	Fleet Clean NC may be used hot or cold via a pressure washer.  For best results use hot.
	<ol><li>Suitable dilutions are normally established by experience. See guidance above.</li></ol>
	<ol> <li>Apply chemical to the surface of the vehicle at low or high, pressure working from the <u>bottom of the vehicle upward</u> to avoid cleaning-streaks.</li> </ol>
	<ol> <li>In hot weather cool paintwork with water <u>before</u> applying chemical. <u>Do not</u> allow the chemical to dry on the surface.</li> </ol>
	<ol> <li>Rinse with a bucket, hose or pressure washer <u>from the top of</u> <u>the vehicle rinsing downwards</u> evenly and methodically.</li> </ol>
Hints & Tips	For the very best results, use warm water (<60°C at machine)
	When applying chemical, to avoid cleaning-streaks, always work from bottom to top of vehicle.
Precautions	Always observe precautions set out in the material safety data sheet.
	For fresh or damaged paint/livery check compatibility on an inconspicuous area first.

Issue Date: 17/07/2018