

User Guide Premium Fleet Clean with Wax

22001099	9/20Lt 22001100/205Lt 22001101/1000Lt IBC
Application	Premium Fleet Clean With Wax
Features & Benefits	 Beading wax rinse – Gleaming Finish Caustic and NTA-Free – Safer to use Excellent performance on all vehicle types Biodegradable formulation
Dilution	Light Soiling: 1% (100:1) Medium Soiling 2% (50:1) Heavy Soiling 3% (30:1)
Equipment Required	 Pressure washer Suitable dilution vessel Bucket/Mop Water supply
Use Instructions	 Premium Fleet Clean with Wax may be used hot or cold via a pressure washer. For best results use hot. Suitable dilutions are normally established by experience. See guidance above. Apply product at low or high pressure working from the bottom upwards. This avoids streaking on cleaned vehicle. In hot weather cool paintwork with water before applying chemical. Do not allow the chemical to dry on the surface. Rinse with a bucket, hose or pressure washer from the top of the vehicle rinsing downwards evenly and methodically.
Hints & Tips	For a perfect spot-free finish dry off with a squeegee or chamois For the very best results, use warm water (<60°C at machine) To avoid cleaning-streaks, always work from bottom to top of vehicle.
Precautions	Always observe precautions in material safety data sheet, For fresh or damaged paint/livery always check compatibility on an inconspicuous area first.

Issue No.

Issue Date: 09-02-2015