

Technical User Guide

RES Sootlock

22000773/2x5Lt

M0171RES

Page 1 of 1

E-mail: info@rozone.co.uk

Tel: 0121 526 8181. Fax: 0121 526 8182

Application	Clear Encapsulation Spray: Prevents Soil & Odour Bleed
Features & Benefits	Dries Clear
	Breathable
	Can be used on many surfaces
	 Excellent coverage 6 to 8 sq m per litre
	 Can be applied wide temperature range (-10°C to +80°C)
	 Quick and easy to apply (Apply above 5°C)
	Non-solvent water-based formulation
Dilution	Product can be used neat or slightly diluted with up to 10% water to aid application
Equipment Required	Polythene sheeting
	Suitable container for decanting/dilution
	Brush/roller
	Air applicator
Use Instructions	Mask off surrounding area .
	2. Surfaces should be clean, dry and free from dust.
	3. Use neat or diluted with up to 10% clean water.
	4. Apply using brush, roller or airless sprayer, leave to dry.
	5. Use 1 litre of product to cover 6 to 8 sqm.
Hints & Tips	Drying time 30 minutes to 4 hours dependent upon substrate absorbency and temperature
	Can be used on exposed wood e.g. joists
Precautions	Use all PPE advised in MSDS and COSHH Assessment
	Keep the application equipment clean – do not allow product to set in applicator.